





## For Maximum Water Coalescing Efficiency and Solids Holding Capacity

Facet CA Series coalescer cartridges offer the finest performance available. This standard line of high flow coalescer cartridges removes ultra-fine solids and enhances separation of water from jet fuel.

Built for balanced fluid flow-thru and structural strength, each CA Series coalescer cartridge is a single-piece construction of various combined media, precisely arranged in many layers and pleats, wrapped around a treated, perforated metal shell —all encased in an outer sock material. All cartridges are 6" (152 mm) outside diameter, the standard model has an inside diameter of 3½" (89 mm) and available in standard interchangeable nominal lengths from from 11¼" (290 mm) to 57¼" (1450 mm).

The CA Series coalescer cartridges are available in two cartridge mounting styles: self-centering rod mount and screw base. The rod mount style has treated metal end caps, while the screw base ends are injection molded, glass-filled nylon. This screw base material offers superior strength and ease of maintenance —uniform threads, no shrinkage, no galling and no gasket to recover.

A permanent affixed Buna-N gasket seals against the V-type knife edge mounting adaptor to provide a positive seal. It will not separate from the cartridge during installation or change out.

#### **Standard Design Features**

- Multi-layered media for increased solids holding capacity
- Ultra-fine solids removal
- Maximum water coalescence
- Balanced cartridge flow characteristics
- Recommended maximum operating temperature: 240°F (115°C)
- Withstand in excess of 75 psi differential pressure
- pH range from 5 to 9
- Screw base or open-end configuration

#### **Materials**

- All metal components are treated against corrosion
- Screw base ends are injection molded, glass-filled nylon with locked-in gaskets
- Buna-N gaskets —other materials are available on request

# CA Series Coalescer Cartridges

### DATA

| MODEL<br>NUMBER | OUTSIDE DIAMETER |     | INSIDE DIAMETER |    | NOMINAL LENGTH |      | MOUNTING   |
|-----------------|------------------|-----|-----------------|----|----------------|------|------------|
|                 | in               | mm  | in              | mm | in             | mm   | STYLE      |
| CA11            | 6                | 152 | 31⁄2            | 89 | 111⁄4          | 290  | Rod        |
| CA14            | 6                | 152 | 31/2            | 89 | 141⁄2          | 370  | Rod        |
| CA14SB          | 6                | 152 | 31/2            | 89 | 15             | 380  | Screw Base |
| CA22            | 6                | 152 | 31/2            | 89 | 221⁄4          | 560  | Rod        |
| CA22SB          | 6                | 152 | 31/2            | 89 | 23             | 580  | Screw Base |
| CA28            | 6                | 152 | 31/2            | 89 | 28¾            | 730  | Rod        |
| CA28SB          | 6                | 152 | 31/2            | 89 | 29             | 740  | Screw Base |
| CA33            | 6                | 152 | 31/2            | 89 | 33¼            | 840  | Rod        |
| CA33SB          | 6                | 152 | 31/2            | 89 | 34             | 860  | Screw Base |
| CA38            | 6                | 152 | 31/2            | 89 | 38             | 960  | Rod        |
| CA38SB          | 6                | 152 | 31/2            | 89 | 39             | 990  | Screw Base |
| CA43            | 6                | 152 | 31/2            | 89 | 431⁄4          | 1100 | Rod        |
| CA43SB          | 6                | 152 | 31/2            | 89 | 45             | 1140 | Screw Base |
| CA56            | 6                | 152 | 31/2            | 89 | 56¼            | 1430 | Rod        |
| CA56SB          | 6                | 152 | 31/2            | 89 | 57             | 1450 | Screw Base |

NOTE: The Facet screw base adaptor part number is 677453A-AM.