

1100FS 1100 FS Product Series Revision Date 15-Jul-2016 Supersedes Date: No information available

Version 5

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product Identifier

Product Name 1100 FS Product Series

Product Code 1100FS

**Product(s) Covered**See section 16 for more information

### 1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended use Adhesives, sealants.
Uses Advised Against No information available

### 1.3. Details of the Supplier of the Safety Data Sheet

## **Company Name**

Bostik, Inc.

11320 W. Watertown Plank Road Wauwatosa, Wisconsin 53226 USA

Phone: +1 (800) 843-0844 (Domestic Toll Free) Phone: +1 (414) 774-2250 (International)

Fax: +1 (414) 774-8075 Email: msds@bostik-us.com

## 1.4. Emergency Telephone Number

**Emergency Telephone** Telephone: 1-800-227-0332

(Outside U.S.) 1-703-527-3887

## Section 2: HAZARD IDENTIFICATION

## 2.1. Classification of the Substance or Mixture

Respiratory sensitization	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 4

## 2.2. Label Elements

#### **EMERGENCY OVERVIEW**

## DANGER

## Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

Suspected of causing cancer

Suspected of damaging fertility or the unborn child

May cause damage to organs through prolonged or repeated exposure

1100FS 1100 FS Product Series Revision Date 15-Jul-2016 Supersedes Date: No information available

Version 5

Combustible liquid



Appearance Paste Physical State Liquid

**Odor** Solvent

### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

In case of inadequate ventilation wear respiratory protection

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

## **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see first aid measures on this label)

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

In case of fire: Use CO2, dry chemical, or foam to extinguish.

### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards Not Otherwise Classified (HNOC)

Not applicable

#### **Unknown Toxicity**

26% of the mixture consists of ingredient(s) of unknown toxicity

### 2.3. Other Information

Causes mild skin irritation.

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1 Substances

This product is a mixture. Health hazard information is based on its components.

#### 3.2 Mixtures

Chemical Name	CAS No	Weight-%
Polyvinyl chloride	9002-86-2	10 - 30

1100FS Revision Date 15-Jul-2016
1100 FS Product Series Supersedes Date: No information available

Version 5

Limestone	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	1 - 5
Propylene carbonate	108-32-7	1 - 5
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	0.1 - 1
Carbon black	1333-86-4	0.1 - 1
4,4'-Methylenediphenyl diisocyanate	101-68-8	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1
Toluene	108-88-3	0.1 - 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

## Section 4: FIRST AID MEASURES

#### 4.1. Description of First Aid Measures

General Advice Remove and isolate contaminated clothing and shoes. Do not breathe

dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. If medical

advice is needed, have product container or label at hand.

Eye contact In case of contact with substance, immediately flush skin or eyes with running water for at

least 20 minutes. Keep eye wide open while rinsing. If eye irritation persists: Get medical

advice/attention.

**Skin Contact**Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Wash contaminated clothing before reuse. May cause sensitization by

skin contact. If skin irritation persists, call a physician.

**Inhalation** Move victim to fresh air. Administer oxygen if breathing is difficult. If breathing is irregular or

stopped, administer artificial respiration.

Ingestion Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Never give anything by mouth

to an unconscious person. Call a physician or poison control center immediately.

Self-protection of the First Aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

## 4.2. Most Important Symptoms and Effects, Both Acute and Delayed

**Symptoms** No information available.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

**Note to physicians** May cause sensitization by inhalation and skin contact.

4.4. Reference to Other Sections

Reference to Other Sections Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 11: TOXICOLOGY INFORMATION

## Section 5: FIRE-FIGHTING MEASURES

## 5.1. Extinguishing Media

### **Suitable Extinguishing Media**

Dry chemical, CO2, water spray or regular foam. Use water spray or fog; do not use straight streams. Move containers from fire area if you can do it without risk.

#### **Unsuitable Extinguishing Media**

1100FS Revision Date 15-Jul-2016
1100 FS Product Series Supersedes Date: No information available

Version 5

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

### 5.2. Special Hazards Arising from the Substance or Mixture

#### **Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. May cause sensitization by inhalation and skin contact.

**Explosion Data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

#### 5.3. Advice for Firefighters

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## Section 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Do not touch or walk through spilled material. All equipment used when handling the product must be grounded. Pay attention to flashback.

Take precautionary measures against static discharges.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

6.2. Environmental Precautions

**Environmental Precautions** Prevent entry into waterways, sewers, basements or confined areas. Prevent product from

entering drains. See Section 12 for additional Ecological Information.

6.3. Methods and Material for Containment and Cleaning up

**Methods for Containment** A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth,

sand or other non-combustible material and transfer to containers. Dike far ahead of liquid

spill for later disposal.

Methods for Cleaning up

Use personal protective equipment as required. Use clean non-sparking tools to collect

absorbed material. Pick up and transfer to properly labeled containers. Do not direct water at spill or source of leak. Decontaminate floor with decontamination solution letting stand for at least 15 minutes. Soak up with inert absorbent material. Take precautionary measures

against static discharges.

6.4. Reference to other sections

Reference to Other Sections Section 7: HANDLING AND STORAGE

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 13: DISPOSAL CONSIDERATIONS

## Section 7: HANDLING AND STORAGE

## 7.1. Precautions for Safe Handling

1100FS 1100 FS Product Series Revision Date 15-Jul-2016 Supersedes Date: No information available

Version 5

\_\_\_\_\_

## **Advice on Safe Handling**

Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Ensure adequate ventilation, especially in confined areas. Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

## 7.2. Conditions for Safe Storage, including any Incompatibilities

Storage Conditions Keep out of the reach of children. Keep in properly labeled containers. Keep away from

heat. Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from

direct contact with water or excessive moisture. Reacts with water.

Incompatible Materials Water. Alcohols. Strong bases. Strong oxidizing agents. Finely powdered metals. Strong

acids. Chlorinated compounds.

7.3. Specific End Use(s)

Other Information No information available.

7.4. References to Other Sections

Reference to Other Sections Section 13: DISPOSAL CONSIDERATIONS

Section 10: STABILITY AND REACTIVITY

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control Parameters

### **Exposure Guidelines**

As Titanium dioxide (13463-67-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Carbon black (1333-86-4) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Limestone CAS 1317-65-3 is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Polyvinyl chloride	TWA: 1 mg/m <sup>3</sup> respirable	-	-	-
9002-86-2	fraction			
Limestone	-	TWA: 10 mg/m³ total dust	TWA: 15 mg/m³ total dust	TWA: 10 mg/m <sup>3</sup>
1317-65-3		TWA: 5 mg/m <sup>3</sup> respirable	TWA: 5 mg/m³ respirable	STEL: 20 mg/m <sup>3</sup>
		dust	fraction	
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	IDLH: 5000 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust	TWA: 10 mg/m <sup>3</sup>
13463-67-7	_	_	_	STEL: 20 mg/m <sup>3</sup>
Xylenes (o-, m-, p- isomers)	STEL: 150 ppm	-	TWA: 100 ppm	TWA: 100 ppm
1330-20-7	TWA: 100 ppm		TWA: 435 mg/m <sup>3</sup>	TWA: 435 mg/m <sup>3</sup>
				STEL: 150 ppm
				STEL: 655 mg/m <sup>3</sup>
Carbon black	TWA: 3 mg/m <sup>3</sup> inhalable	IDLH: 1750 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>
1333-86-4	fraction	TWA: 3.5 mg/m <sup>3</sup>		STEL: 7 mg/m <sup>3</sup>
		TWA: 0.1 mg/m <sup>3</sup> Carbon		
		black in presence of		
		Polycyclic aromatic		
		hydrocarbons PAH		
4,4'-Methylenediphenyl	TWA: 0.005 ppm	IDLH: 75 mg/m <sup>3</sup>	Ceiling: 0.02 ppm	-
diisocyanate		Ceiling: 0.020 ppm 10 min	Ceiling: 0.2 mg/m <sup>3</sup>	
101-68-8		Ceiling: 0.2 mg/m <sup>3</sup> 10 min		

1100FS Revision Date 15-Jul-2016 1100 FS Product Series Supersedes Date: No information available

Version 5

		TWA: 0.005 ppm TWA: 0.05 mg/m <sup>3</sup>		
Ethylbenzene 100-41-4	TWA: 20 ppm	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³	TWA: 100 ppm TWA: 435 mg/m³	TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³
Toluene 108-88-3	TWA: 20 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>	TWA: 200 ppm Ceiling: 300 ppm	TWA: 50 ppm TWA: 188 mg/m³

Chemical Name	Argentina	Brazil	Chile	Venezuela
Limestone 1317-65-3	TWA: 10 mg/m <sup>3</sup>	-	TWA: 8 mg/m <sup>3</sup>	-
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	-	-	TWA: 10 mg/m <sup>3</sup>
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 78 ppm TWA: 340 mg/m <sup>3</sup>	TWA: 80 ppm TWA: 347 mg/m <sup>3</sup>	Skin STEL: 150 ppm TWA: 100 ppm
Carbon black 1333-86-4	TWA: 3.5 mg/m <sup>3</sup>	-	-	TWA: 3.5 mg/m <sup>3</sup>
4,4'-Methylenediphenyl diisocyanate 101-68-8	<del>-</del>	-	-	TWA: 0.005 ppm
Ethylbenzene 100-41-4	TWA: 100 ppm STEL: 125 ppm	TWA: 78 ppm TWA: 340 mg/m <sup>3</sup>	TWA: 80 ppm TWA: 348 mg/m³	Skin STEL: 125 ppm TWA: 100 ppm
Toluene 108-88-3	TWA: 50 ppm Skin	TWA: 78 ppm TWA: 290 mg/m³ Skin	TWA: 80 ppm TWA: 300 mg/m³ Skin	Skin TWA: 20 ppm

#### 8.2. Exposure Controls

**Engineering Controls** Showers

Evewash stations Ventilation systems.

Personal protective equipment [PPE]

**Respiratory Protection** 

Tight sealing safety goggles. Wear safety glasses with side shields (or goggles). Face **Eye/Face Protection** 

protection shield.

Wear suitable chemical resistant gloves. The selection of suitable gloves does not only **Skin and Body Protection** 

depend on the material, but also on further marks of quality and various manufacturers. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be

required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

**Physical State** Liquid Paste **Appearance** 

Multiple Colors Color Solvent Odor

**Odor Threshold** 

No information available

1100FS 1100 FS Product Series Revision Date 15-Jul-2016
Supersedes Date: No information available

Not applicable for liquids

Version 5

Property Values Remarks • Method

pH No information available
Melting Point/Freezing Point No information available
Boiling Point No information available
Flash Point 71.1 °C / 160 °F
Evaporation Rate No information available
Flammability (solid, gas) No information available

Flammability Limit in Air

Upper Flammability Limit
Lower Flammability Limit
Vapor Pressure
Vapor Density
Specific Gravity
Water Solubility

No information available

**Solubility in Other Solvents** 

Partition CoefficientNo information availableAutoignition TemperatureNo information availableDecomposition TemperatureNo information availableKinematic ViscosityNo information available

Dynamic ViscosityNo information availableExplosive PropertiesNo information availableOxidizing PropertiesNo information available

9.2. Other Information

Softening PointNo information availableMolecular WeightNo information availableSolvent Content (%)No information available

 Solid Content (%)
 96.0

 Density
 1.215 g/cm³

 VOC
 2.7 %

## Section 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None under normal use conditions.

## 10.2. Chemical Stability

Stable under recommended storage conditions.

## 10.3. Possibility of Hazardous Reactions

None under normal processing.

**Hazardous Polymerization** Hazardous polymerization may occur.

### 10.4. Conditions to Avoid

Keep from any possible contact with water. Extremes of temperature and direct sunlight. Storage near to reactive materials. Heat, flames and sparks.

#### 10.5. Incompatible Materials

Water. Alcohols. Strong bases. Strong oxidizing agents. Finely powdered metals. Strong acids. Chlorinated compounds.

1100FS Revision Date 15-Jul-2016
1100 FS Product Series Supersedes Date: No information available

Version 5

\_\_\_\_\_

## 10.6. Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Hydrogen cyanide. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Carbon oxides.

## Section 11: TOXICOLOGY INFORMATION

#### 11.1. Information on Toxicological Effects

Product InformationNo Data AvailableInhalationNo Data AvailableEye contactNo Data AvailableSkin ContactNo Data AvailableIngestionNo Data Available

### **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (rat)	-	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Propylene carbonate 108-32-7	= 29000 mg/kg (Rat)	> 20 mL/kg(Rabbit)	-
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= >47635 mg/L (Rat) 4 h = >5000 ppm (Rat) 4 h
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	= 2234 mg/kg(Rat)	-	> 640 ppm (Rat) 1 h
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg(Rabbit)	-
4,4'-Methylenediphenyl diisocyanate 101-68-8	= 31600 mg/kg (Rat) = 9200 mg/kg (Rat)	-	= 369 mg/m³ ( Rat ) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg(Rabbit)	= 1432 mg/L (Rat) 4 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg(Rabbit)	= 30 mg/L (Rat) 4 h

## Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Symptoms
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Irritation
Corrosivity
Sensitization
Germ Cell Mutagenicity
No information available.

Reproductive Toxicity Product is or contains a chemical which is a known or suspected reproductive hazard.

Developmental ToxicityNo information available.TeratogenicityNo information available.STOT - Single ExposureNo information available.STOT - Repeated ExposureNo information available.

Chronic Toxicity Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated

exposure. Repeated or prolonged exposure may cause central nervous system damage. Repeated or prolonged contact causes sensitization, asthma and eczemas. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver

effects. Contains a known or suspected reproductive toxin.

Target Organ Effects Respiratory system, Eyes, Skin, Central nervous system, Blood, Gastrointestinal tract (GI),

Kidney, Liver, Lungs.

1100FS 1100 FS Product Series Revision Date 15-Jul-2016 Supersedes Date: No information available

Version 5

Aspiration Hazard Carcinogenicity

No information available.

The table below indicates whether each agency has listed any ingredient as a carcinogen. As Titanium dioxide (13463-67-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Carbon black (1333-86-4) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

Chemical Name	ACGIH	IARC	NTP	OSHA
Polyvinyl chloride 9002-86-2	-	Group 3	-	-
Titanium dioxide 13463-67-7	-	Group 2B	-	X
Xylenes (o-, m-, p- isomers) 1330-20-7	-	Group 3	-	-
Carbon black 1333-86-4	A3	Group 2B	-	Х
4,4'-Methylenediphenyl diisocyanate 101-68-8	<del>-</del>	Group 3	-	-
Ethylbenzene 100-41-4	A3	Group 2B	-	Х
Toluene 108-88-3	-	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Confirmed animal carcinogen with unknown relevance to humans

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

## Section 12: ECOLOGICAL INFORMATION

## 12.1. Toxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
Limestone	CE50 (72h) >200mg/L Algae	CL50 (96h)>10000mg/L Fish		CE50 (48h) >1000 mg/L
1317-65-3	(Desmondesmus subspicatus)	(Oncorhynchus mykiss)		Daphnia Magna
Propylene carbonate	EC50 72 h > 500 mg/L	LC50 96 h = 5300 mg/L	EC50 > 10000 mg/L 17 h	EC50 48 h > 500 mg/L
108-32-7	(Desmodesmus	(Leuciscus idus static) LC50	_	(Daphnia magna )
	subspicatus)	96 h > 1000 mg/L (Cyprinus carpio semi-static)		
Vidence (c. m. n. icemera)		LC50 96 h 23.53 - 29.97	FCF0 0.0004 mg/l 24 h	EC50 48 h = 3.4 mg/L (water
Xylenes (o-, m-, p- isomers) 1330-20-7			EC50 = 0.0084 mg/L 24 h	J (
1330-20-7		mg/L (Pimephales promelas static) LC50 96 h 13.5 -		flea)
		17.3 mg/L (Oncorhynchus		
		mykiss ) LC50 96 h = 19		
		mg/L (Lepomis macrochirus		
		) LC50 96 h > 780 mg/L		
		(Cyprinus carpio ) LC50 96 h		
		30.26 - 40.75 mg/L (Poecilia		
		reticulata static) LC50 96 h =		
		13.4 mg/L (Pimephales		
		promelas flow-through)		

1100FS 1100 FS Product Series Revision Date 15-Jul-2016 Supersedes Date: No information available

Version 5

Carbon black 1333-86-4 4,4'-Methylenediphenyl	>10000 mg/l (Desmodesmus subspicatus) OECD 202	LC50 96 h = 780 mg/L (Cyprinus carpio semi-static) LC50 96 h 2.661 - 4.093 mg/L (Oncorhynchus mykiss static) LC50 96 h 13.1 - 16.5 mg/L (Lepomis macrochirus flow-through) LC50 96 h 7.711 - 9.591 mg/L (Lepomis macrochirus static) >1000 mg/l (Brachydanio rerio) OCDE 203 >1000 mg/l (Danio rerio)		EC50 24 h > 5600 mg/L (Daphnia magna )
diisocyanate				
101-68-8 Ethylbenzene 100-41-4	EC50 96 h > 438 mg/L (Pseudokirchneriella subcapitata) EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata) EC50 96 h 1.7 - 7.6 mg/L (Pseudokirchneriella subcapitata) EC50 72 h = 4.6 mg/L (Pseudokirchneriella subcapitata) (Pseudokirchneriella subcapitata)	LC50 96 h = 32 mg/L (Lepomis macrochirus static) LC50 96 h 9.1 - 15.6 mg/L (Pimephales promelas static) LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static) LC50 96 h 11.0 - 18.0 mg/L (Oncorhynchus mykiss static) LC50 96 h 7.55 - 11 mg/L (Pimephales promelas flow-through) LC50 96 h = 9.6 mg/L (Poecilia reticulata static)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h 1.8 - 2.4 mg/L (Daphnia magna )
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata) EC50 96 h > 433 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static) LC50 96 h = 12.6 mg/L (Pimephales promelas static) LC50 96 h 11.0 - 15.0 mg/L (Lepomis macrochirus static) LC50 96 h = 54 mg/L (Oryzias latipes static) LC50 96 h 15.22 - 19.05 mg/L (Pimephales promelas flow-through) LC50 96 h 50.87 - 70.34 mg/L (Poecilia reticulata static) LC50 96 h 14.1 - 17.16 mg/L (Oncorhynchus mykiss static) LC50 96 h = 28.2 mg/L (Poecilia reticulata semi-static)	EC50 = 19.7 mg/L 30 min	EC50 48 h 5.46 - 9.83 mg/L (Daphnia magna Static) EC50 48 h = 11.5 mg/L (Daphnia magna )

## 12.2. Persistence and Degradability

No information available.

### 12.3. Bioaccumulative Potential

No information available.

## 12.4. Mobility in Soil

No information available.

## 12.5 Other adverse effects

No information available

1100FS Revision Date 15-Jul-2016
1100 FS Product Series Supersedes Date: No information available

Version 5

## Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

**Disposal of Wastes**It is the responsibility of the waste generator to determine the toxicity and physical

properties of the material generated to determine the proper waste identification and

disposal methods in compliance with applicable regulations

Contaminated Packaging Dispose of in accordance with federal, state and local regulations

Section 14: TRANSPORTATION INFORMATION

**Note:** 49 CFR 173.150(f)(2) "The requirements in this subchapter do not apply to a material

classed as a combustible liquid in a non-bulk packaging unless the combustible liquid is a

hazardous substance, a hazardous waste, or a marine pollutant."

DOT

UN/ID No NA1993

**Proper Shipping Name**Hazard Class
Combustible liquid, n.o.s.
Combustible liquid

Packing Group

Special Provisions IB3, T1, T4, TP1

Description NA1993, Combustible liquid, n.o.s. (Xylenes), Combustible liquid, III,

Emergency Response Guide 128

Number

<u>IATA</u> Not regulated

IMDG Not regulated

## Section 15: REGULATORY INFORMATION

## **Global Inventories**

TSCA	Listed
DSL	Listed

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

## **WHMIS Hazard Class**

B3 - Combustible liquid D2A - Very toxic materials



1100FS 1100 FS Product Series Revision Date 15-Jul-2016

Supersedes Date: No information available

Version 5

## **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No
Xylenes (o-, m-, p- isomers)	1330-20-7
Ethylbenzene	100-41-4

## SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	yes
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

## **California Proposition 65**

This product contains one or more of the substances listed on Proposition 65 at or above 0.01 wt. %

Chemical Name	CAS No
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	68515-49-1
Titanium dioxide	13463-67-7
Carbon black	1333-86-4
Ethylbenzene	100-41-4
Toluene	108-88-3
Quartz	14808-60-7
Cumene	98-82-8

### **Europe**

## Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation.

# EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Section 16: OTHER INFORMATION

#### Product(s) Covered

A19200-7C	1100FS wht MP5GL/P24
A19200-95	1100FS wht MD530LB(52GL)/P3
A19200-95L	1100FS wht MD52GL(533LB)/P3
A19217	1100FS wht FCt10.10Z/C24
A19217-95L	1100FS wht MD52GL(533LB)/P3
A19221	1100FS wht Sau20OZ/C12
A25600-7C	1100FS blk MP5GL/P24
A25614	1100FS blk FCt10.10Z/C24
A25614-95L	1100FS blk MD52GL(520LB)/P3
A26815	1100FS gry FCt10.1OZ/C24
A26815-95L	1100FS gry MD52GL(530LB)/P3

HMIS Health Hazards 2\* Flammability 2 Physical Hazards 0 Personal Protection X

1100FS 1100 FS Product Series Revision Date 15-Jul-2016
Supersedes Date: No information available

Version 5

\_\_\_\_\_

## Key or Legend to Abbreviations and Acronyms Used in the Safety Data Sheet

No information available

#### **Key Literature References and Sources for Data**

No information available

Prepared By Product Safety & Regulatory Affairs

Revision Date 15-Jul-2016

Revision Note Not applicable.

Training Advice No information available

Additional information No information available

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**